



Úzké klínové řemeny CONTI-V ADVANCE

Narrow V-Belts CONTI-V ADVANCE

ADVANCE


DIN 7753/1, ISO 4184

Objednací číslo / Part.No.

SPC2500 Ld ADVANCE

SPC... Profil / profile

2500... Účinná délka / Belt length



Profil $b_0 \times h$ (mm)

SPZ 9,7 x 8

SPA 12,7 x 10

SPB/5V 16,3 x 13

SPC 22 x 18



zesílená polyesterová vlákna, více než o 40% vyšší přenášený výkon, vyšší účinnost, delší životnost /
reinforced polyester tension member, over 40% greater performance, higher efficiency, longer service life



Typ CONTI-V ADVANCE - Profil SPZ, SPA, SPB, SPC ADVANCE - DIN 7753/1

Typ řemenu / Part.No. Účinná délka Ld [mm] Datum length Ld [mm]	Typ řemenu / Part.No. Účinná délka Ld [mm] Datum length Ld [mm]	Typ řemenu / Part.No. Účinná délka Ld [mm] Datum length Ld [mm]	Typ řemenu / Part.No. Účinná délka Ld [mm] Datum length Ld [mm]
SPZ ADVANCE	SPZ ADVANCE	SPA ADVANCE	SPA ADVANCE
SPZ 1202 ADVANCE	SPZ 2800 ADVANCE	SPA 1207 ADVANCE	SPA 2182 ADVANCE
SPZ 1212 ADVANCE	SPZ 3000 ADVANCE	SPA 1232 ADVANCE	SPA 2207 ADVANCE
SPZ 1237 ADVANCE	SPZ 3150 ADVANCE	SPA 1250 ADVANCE	SPA 2232 ADVANCE
SPZ 1250 ADVANCE	SPZ 3350 ADVANCE	SPA 1257 ADVANCE	SPA 2240 ADVANCE
SPZ 1262 ADVANCE	SPZ 3550 ADVANCE	SPA 1272 ADVANCE	SPA 2282 ADVANCE
SPZ 1287 ADVANCE		SPA 1282 ADVANCE	SPA 2300 ADVANCE
SPZ 1312 ADVANCE		SPA 1307 ADVANCE	SPA 2307 ADVANCE
SPZ 1320 ADVANCE		SPA 1320 ADVANCE	SPA 2332 ADVANCE
SPZ 1337 ADVANCE		SPA 1332 ADVANCE	SPA 2360 ADVANCE
SPZ 1362 ADVANCE		SPA 1357 ADVANCE	SPA 2382 ADVANCE
SPZ 1387 ADVANCE		SPA 1382 ADVANCE	SPA 2432 ADVANCE
SPZ 1400 ADVANCE		SPA 1400 ADVANCE	SPA 2482 ADVANCE
SPZ 1412 ADVANCE		SPA 1407 ADVANCE	SPA 2500 ADVANCE
SPZ 1437 ADVANCE		SPA 1432 ADVANCE	SPA 2532 ADVANCE
SPZ 1462 ADVANCE		SPA 1457 ADVANCE	SPA 2582 ADVANCE
SPZ 1487 ADVANCE		SPA 1482 ADVANCE	SPA 2607 ADVANCE
SPZ 1500 ADVANCE		SPA 1500 ADVANCE	SPA 2632 ADVANCE
SPZ 1512 ADVANCE		SPA 1507 ADVANCE	SPA 2650 ADVANCE
SPZ 1537 ADVANCE		SPA 1532 ADVANCE	SPA 2682 ADVANCE
SPZ 1562 ADVANCE	Ld max. SPZ = 3550 mm	SPA 1557 ADVANCE	SPA 2732 ADVANCE
SPZ 1587 ADVANCE	Li = Ld - 38 mm	SPA 1582 ADVANCE	SPA 2782 ADVANCE
SPZ 1600 ADVANCE	La = Ld + 12 mm	SPA 1600 ADVANCE	SPA 2800 ADVANCE
SPZ 1612 ADVANCE	La = Li + 50 mm	SPA 1607 ADVANCE	SPA 2832 ADVANCE
SPZ 1637 ADVANCE		SPA 1632 ADVANCE	SPA 2847 ADVANCE
SPZ 1662 ADVANCE	Hmotnost řemenu/ Belt weight = 0,073 kg/m	SPA 1657 ADVANCE	SPA 2882 ADVANCE
SPZ 1687 ADVANCE	Min. průměr řemenice 63 mm	SPA 1682 ADVANCE	SPA 2932 ADVANCE
SPZ 1700 ADVANCE	Min. pulley diameter 63 mm	SPA 1700 ADVANCE	SPA 2982 ADVANCE
SPZ 1737 ADVANCE		SPA 1707 ADVANCE	SPA 3000 ADVANCE
SPZ 1762 ADVANCE		SPA 1732 ADVANCE	SPA 3032 ADVANCE
SPZ 1787 ADVANCE		SPA 1757 ADVANCE	SPA 3082 ADVANCE
SPZ 1800 ADVANCE		SPA 1782 ADVANCE	SPA 3150 ADVANCE
SPZ 1837 ADVANCE		SPA 1800 ADVANCE	SPA 3182 ADVANCE
SPZ 1862 ADVANCE	Ld max. SPA = 4500 mm	SPA 1807 ADVANCE	SPA 3282 ADVANCE
SPZ 1887 ADVANCE	Li = Ld - 46 mm	SPA 1832 ADVANCE	SPA 3350 ADVANCE
SPZ 1900 ADVANCE	La = Ld + 17 mm	SPA 1857 ADVANCE	SPA 3382 ADVANCE
SPZ 1937 ADVANCE	La = Li + 63 mm	SPA 1882 ADVANCE	SPA 3482 ADVANCE
SPZ 1987 ADVANCE		SPA 1900 ADVANCE	SPA 3550 ADVANCE
SPZ 2000 ADVANCE	Hmotnost řemenu/ Belt weight = 0,100 kg/m	SPA 1907 ADVANCE	SPA 3650 ADVANCE
SPZ 2037 ADVANCE	Min. průměr řemenice 90 mm	SPA 1932 ADVANCE	SPA 3750 ADVANCE
SPZ 2120 ADVANCE	Min. pulley diameter 90 mm	SPA 1957 ADVANCE	SPA 3870 ADVANCE
SPZ 2137 ADVANCE		SPA 1982 ADVANCE	SPA 4000 ADVANCE
SPZ 2187 ADVANCE		SPA 2000 ADVANCE	SPA 4250 ADVANCE
SPZ 2240 ADVANCE		SPA 2032 ADVANCE	SPA 4500 ADVANCE
SPZ 2287 ADVANCE	Ld = účinná délka / datum length	SPA 2057 ADVANCE	
SPZ 2360 ADVANCE	Li = vnitřní délka / inside length	SPA 2082 ADVANCE	
SPZ 2500 ADVANCE	La = vnější délka / outside length	SPA 2120 ADVANCE	
SPZ 2650 ADVANCE		SPA 2132 ADVANCE	

Řemeny lze použít se standardními řemenicemi SPZ-SPA-SPB-SPC. / Belts can be used with standard pulleys SPZ-SPA-SPB-SPC.



Úzké klínové řemeny CONTI-V ADVANCE

Narrow V-Belts CONTI-V ADVANCE

ADVANCE


DIN 7753/1, ISO 4184

Objednáací číslo / Part.No.

SPC2500 Ld ADVANCE

SPC... Profil / profile

2500... Účinná délka / Belt length



Profil $b_0 \times h$ (mm)

SPZ 9,7 x 8

SPA 12,7 x 10

SPB/5V 16,3 x 13

SPC 22 x 18



zesílená polyesterová vlákna, více než o 40% vyšší přenášený výkon, vyšší účinnost, delší životnost /
reinforced polyester tension member, over 40% greater performance, higher efficiency, longer service life



Typ CONTI-V ADVANCE - Profil SPZ, SPA, SPB, SPC ADVANCE - DIN 7753/1

Typ řemenu / Part.No. Účinná délka Ld [mm] Datum length Ld [mm]	Typ řemenu / Part.No. Účinná délka Ld [mm] Datum length Ld [mm]	Typ řemenu / Part.No. Účinná délka Ld [mm] Datum length Ld [mm]	
SPB ADVANCE	SPB ADVANCE	SPC ADVANCE	
SPB 1250 ADVANCE	SPB 4820 ADVANCE	SPC 2000 ADVANCE	
SPB 1320 ADVANCE	SPB 5000 ADVANCE	SPC 2120 ADVANCE	
SPB 1400 ADVANCE	SPB 5070 ADVANCE	SPC 2240 ADVANCE	
SPB 1450 ADVANCE	SPB 5300 ADVANCE	SPC 2360 ADVANCE	
SPB 1500 ADVANCE	SPB 5380 ADVANCE	SPC 2500 ADVANCE	
SPB 1550 ADVANCE	SPB 5500 ADVANCE	SPC 2650 ADVANCE	
SPB 1600 ADVANCE	SPB 5600 ADVANCE	SPC 2800 ADVANCE	
SPB 1700 ADVANCE	SPB 5680 ADVANCE	SPC 3000 ADVANCE	
SPB 1725 ADVANCE	SPB 6000 ADVANCE	SPC 3150 ADVANCE	
SPB 1800 ADVANCE	SPB 6300 ADVANCE	SPC 3350 ADVANCE	
SPB 1900 ADVANCE	SPB 6700 ADVANCE	SPC 3550 ADVANCE	
SPB 2000 ADVANCE	SPB 7100 ADVANCE	SPC 3750 ADVANCE	
SPB 2020 ADVANCE	SPB 7500 ADVANCE	SPC 4000 ADVANCE	
SPB 2120 ADVANCE	SPB 8000 ADVANCE	SPC 4250 ADVANCE	
SPB 2150 ADVANCE	SPB 9000 ADVANCE	SPC 4500 ADVANCE	
SPB 2240 ADVANCE		SPC 4750 ADVANCE	
SPB 2280 ADVANCE		SPC 5000 ADVANCE	
SPB 2360 ADVANCE		SPC 5300 ADVANCE	
SPB 2500 ADVANCE		SPC 5600 ADVANCE	
SPB 2650 ADVANCE		SPC 6000 ADVANCE	
SPB 2800 ADVANCE		SPC 6300 ADVANCE	
SPB 2900 ADVANCE		SPC 6700 ADVANCE	
SPB 3000 ADVANCE		SPC 7100 ADVANCE	
SPB 3070 ADVANCE		SPC 7500 ADVANCE	
SPB 3150 ADVANCE		SPC 8000 ADVANCE	
SPB 3170 ADVANCE		SPC 8500 ADVANCE	
SPB 3250 ADVANCE		SPC 8700 ADVANCE	
SPB 3350 ADVANCE		SPC 9000 ADVANCE	
SPB 3450 ADVANCE		SPC 9500 ADVANCE	
SPB 3500 ADVANCE			
SPB 3550 ADVANCE			
SPB 3650 ADVANCE			
SPB 3675 ADVANCE			
SPB 3750 ADVANCE			
SPB 3800 ADVANCE			
SPB 3870 ADVANCE			
SPB 4000 ADVANCE	Ld max. SPB = 9000 mm	Ld max. SPC = 9500 mm	Řemeny SPB a SPC lze vyrobit také v provedení POWER s kevlarovými vlákny. / V-belts SPB and SPC can be produced in variant POWER with aramid tensile member.
SPB 4060 ADVANCE	Li = Ld - 60 mm	Li = Ld - 84 mm	
SPB 4120 ADVANCE	La = Ld + 22 mm	La = Ld + 29 mm	
SPB 4250 ADVANCE	La = Li + 82 mm	La = Li + 113 mm	
SPB 4310 ADVANCE			
SPB 4370 ADVANCE	Hmotnost řemenu /	Hmotnost řemenu /	
SPB 4500 ADVANCE	Belt weight = 0,178 kg/m	Belt weight = 0,380 kg/m	
SPB 4560 ADVANCE	Min. průměr řemenice 140 mm	Min. průměr řemenice 225 mm	
SPB 4620 ADVANCE	Min. pulley diameter 140 mm	Min. pulley diameter 225 mm	
SPB 4680 ADVANCE			
SPB 4750 ADVANCE			
			Ld = účinná délka / datum length Li = vnitřní délka / inside length La = vnější délka / outside length

Řemeny lze použít se standardními řemenicemi SPZ-SPA-SPB-SPC. / Belts can be used with standard pulleys SPZ-SPA-SPB-SPC.