

## V-belts

### PU95A beige, reinforced Polyester

notched version possible 



approx. 95° Shore A










Recommended pretension

0,5...2 %

Order No.	Profile dimension mm	Cross section cm <sup>2</sup>	approx. weight kg/100m	Standard roll		Recommended Min. pulley Ø		Fmax/belt (Standard)		Fmax/belt (Overlap)	
				m	ft	mm	inch	kg	lbs	kg	lbs
FBKM13ABGA	13 x 8 (A)	0,82	10,0	50	164	130	5,0	40,0	88,0	67,5	148,5
*FBZKP95A13PV	13 x 8 (A)	0,82	10,0	50	164	100	3,9	34,0	74,8	n/a	n/a
FBKM17BBGA	17 x 11 (B)	1,46	18,0	50	164	175	6,8	72,0	158,4	120,0	264,0
*FBZKP95A17PV	17 x 11 (B)	1,46	18,0	50	164	130	5,0	61,2	134,6	n/a	n/a
FBKM22CBGA	22 x 14 (C)	2,40	29,0	50	164	250	9,7	120,0	264,0	202,0	444,4
*FBZKP95A22PV	22 x 14 (C)	2,40	29,0	50	164	190	7,4	102,0	224,4	n/a	n/a

Coeff. of friction  $\mu$ : Steel: approx. 0,45 | PE: approx. 0,25 | HDPE: approx. 0,20 | \*gezahnt

### Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms	Belt made of 2 components enables combination of hardness and features.

## V-belts

### PU95A beige, reinforced Polyester

notched version possible 



approx. 95° Shore A










Recommended pretension

0,5...2 %

Order No.	Profile dimension mm	Cross section cm <sup>2</sup>	approx. weight kg/100m	Standard roll		Recommended Min. pulley Ø		Fmax/belt (Standard)		Fmax/belt (Overlap)	
				m	ft	mm	inch	kg	lbs	kg	lbs
FBKM13ABGA	13 x 8 (A)	0,82	10,0	50	164	130	5,0	40,0	88,0	67,5	148,5
*FBZKP95A13PV	13 x 8 (A)	0,82	10,0	50	164	100	3,9	34,0	74,8	n/a	n/a
FBKM17BBGA	17 x 11 (B)	1,46	18,0	50	164	175	6,8	72,0	158,4	120,0	264,0
*FBZKP95A17PV	17 x 11 (B)	1,46	18,0	50	164	130	5,0	61,2	134,6	n/a	n/a
FBKM22CBGA	22 x 14 (C)	2,40	29,0	50	164	250	9,7	120,0	264,0	202,0	444,4
*FBZKP95A22PV	22 x 14 (C)	2,40	29,0	50	164	190	7,4	102,0	224,4	n/a	n/a

Coeff. of friction  $\mu$ : Steel: approx. 0,45 | PE: approx. 0,25 | HDPE: approx. 0,20 | \*gezahnt

### Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms	Belt made of 2 components enables combination of hardness and features.