



Dvouřadé podle DIN 8187 / ISO 606 / Duplex according to ISO 606

HFS - High Fatigue Strength

Označení / Type	p	b ₁	d ₄	d ₁	l	k	S _i	S _a	g	e	f	Síla k přetržení	Hmotnost	
ISO	p × b1											Breaking load	Weight	
	palce/inch (mm)	mm	mm	mm	mm	mm	mm	mm	mm	mm	cm ²	N	kg/m	
08B-2 HFS	1/2" × 5/16"	12,7	7,75	8,51	4,45	31	1,6	1,5	1,5	11,8	13,92	1,01	37600	1,45
10B-2 HFS	5/8" × 3/8"	15,875	9,65	10,16	5,08	36,2	2,7	1,65	1,65	14,7	16,59	1,34	52600	1,93
12B-2 HFS	3/4" × 29/64"	19,05	11,68	12,07	5,72	42,2	3	1,8	1,8	16,1	19,46	1,79	61000	2,49
16B-2 HFS	1" × 17,02 mm	25,4	17,02	15,88	8,28	68	3,4	4	3,2	21	31,88	4,21	145000	5,28
20B-2 HFS	1 1/4" × 3/4"	31,75	19,56	19,05	10,19	79	5,1	4,5	3,5	26,4	36,45	5,91	219800	7,78
24B-2 HFS	1 1/2" × 1"	38,1	25,4	25,4	14,63	101	6,7	6	4,7	33,4	48,36	11,08	356600	14,31
28B-2 HFS	1 3/4" × 1 1/4"	44,45	30,99	27,94	15,9	124	5,5	7,4	6	37	59,56	14,79	490000	19,00
32B-2 HFS	2" × 1 1/4"	50,8	30,99	29,21	17,81	126	3,8	6,9	6	42,2	58,55	16,21	544800	19,59
40B-2 HFS	2 1/2" × 1 1/2"	63,5	38,1	39,37	22,85	153	7,4	8,5	8	52,96	72,29	25,5	800000	33,00
48B-2 HFS	3" × 1 3/4"	76,2	45,72	48,2	29,2	190,4	7,6	12	10	64	91,21	41,23	1200000	54,00
56B-2 HFS	3 1/2"	88,9	53,34	54	34,3	221,5	11,5	14	12	78	106,6	55,8	1600000	75,00
64B-2 HFS	4"	101,6	60,96	63,5	39,4	250	10	15	14	93,3	119,89	72,5	2100000	100,00
72B-2 HFS	4 1/2"	114,3	68,58	72,39	44,5	282,8	10,7	18	15	103,63	136,27	92,4	2700000	129,00