



Dvouřadé podle DIN 8188 / ISO 606 / Duplex according to ISO 606

HFS - High Fatigue Strength

Označení /	Type	p		b ₁	d ₄	d ₁	l	k	S _i	S _a	g	e	f	Síla k přetržení	Hmotnost
ISO	ANSI	Rozteč/pitch												Breaking load	Weight
		inch	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	cm ²	N	kg/m
*06C-2	HFS 35-2	3/8"	9,5	4,78	5,08	3,59	22,28	1,58	1,28	1,28	9,04	10,13	0,27	20500	0,63
08A-2	HFS 40-2	1/2"	12,7	7,9	7,9	3,97	30,78	2,4	1,5	1,5	12,06	14,38	0,88	33300	1,22
10A-2	HFS 50-2	5/8"	15,875	9,5	10,14	5,03	38,2	2,4	2	2	15,08	18,11	1,4	54800	2,00
12A-2	HFS 60-2	3/4"	19,05	12,7	11,88	5,95	48	2,72	2,4	2,4	18,09	22,78	2,1	76400	2,87
16A-2	HFS 80-2	1"	25,4	15,85	15,4	7,93	61,96	4,1	3,2	3,2	24,13	29,29	3,56	145000	5,05
20A-2	HFS 100-2	1 1/4"	31,75	19,1	19,04	9,53	75,8	4,3	4	4	30,16	35,76	5,22	235800	7,86
24A-2	HFS 120-2	1 1/2"	38,1	25,4	22,2	11,11	95,86	4,37	4,8	4,8	36,19	45,44	7,84	284200	11,20
28A-2	HFS 140-2	1 3/4"	44,45	25,4	25,39	12,7	103,5	7,4	5,6	5,6	42,22	48,87	9,4	382200	15,35
32A-2	HFS 160-2	2"	50,8	31,55	28,58	14,29	124	4,3	6,4	6,4	48	58,55	19,26	520000	19,23
36A-2	HFS 180-2	2 1/4"	57,15	35,48	35,7	17,46	139,1	5,5	7,2	7,2	53,6	65,84	12,72	630000	26,41
40A-2	HFS 200-2	2 1/2"	63,5	54,94	39,68	19,84	152	6	8	8	60	71,55	32,2	840000	33,94
48A-2	HFS 240-2	3"	76,2	47,63	47,63	23,8	185	9	9,5	9,5	71	78,83	31,7	1352000	46,00

* s rovnými destičkami / with Straight Plates