



**Dvouřadé podle DIN 8187 / ISO 606 / Duplex according to ISO 606**

**SS - Stainless Steel**

Označení / Type	p	b <sub>1</sub>	d <sub>4</sub>	d <sub>1</sub>	l	k	S <sub>1</sub>	S <sub>a</sub>	g	e	f	Síla k přetržení	Hmotnost	
ISO	p × b <sub>1</sub>											Breaking load	Weight	
	palce/inch (mm)	mm	mm	mm	mm	mm	mm	mm	mm	mm	cm <sup>2</sup>	N	kg/m	
05B-2 SS	8 × 3 mm	8	3,04	5	2,31	13,6	0,7	0,76	0,76	7	5,64	0,22	7800	0,35
*06B-2 SS	3/8" × 7/32"	9,525	5,72	6,35	3,28	23,8	2	1,3	1,1	8,2	10,24	0,56	11600	0,74
08B-2 SS	1/2" × 5/16"	12,7	7,75	8,51	4,45	31	1,3	1,5	1,5	11,75	13,92	1,01	21400	1,34
10B-2 SS	5/8" × 3/8"	15,875	9,65	10,16	5,08	36,2	2	1,65	1,65	14,65	15,69	1,34	29400	1,81
12B-2 SS	3/4" × 29/64"	19,05	11,68	12,07	5,72	42,2	1,4	1,8	1,8	16,1	19,46	1,79	37200	2,40
16B-2 SS	1" × 17,02 mm	25,4	17,02	15,88	8,28	68	3,6	4	3,2	20,4	31,88	4,24	78400	5,28
16B-2 SS SP	1" × 17,02 mm	25,4	17,02	15,88	8,28	68	3,6	4	3,2	21	31,88	4,24	78400	5,80
20B-2 SS	1 1/4" × 3/4"	31,75	19,58	19,05	10,19	77,2	3,5	4,5	3,5	26,3	36,45	5,91	170000	7,97
24B-2 SS	1 1/2" × 1"	38,1	25,4	25,4	14,63	101,6	4,7	6	4,8	33,3	48,36	11,09	280000	14,10

\* s rovnými destičkami / with Straight Plates